



World leader in storage solutions

Horizontal silos



HORIZONTAL SILOS SERIES "OR" HIGH CAPACITY

Horizontal silos particularly suitable for mobile construction sites.


The advantages of the series "or" are the follows:


- ▶ Filter (patented system) placed in a position for which the material falls inside the silo.
- ▶ No need of permission for installation,
- ► Minimal environmental impact
- ▶ Quick and easy disassembling, moving and reassembling in another site, with no need of cranes
- ► Extreme flexibility of the unloading positions, the auger being rotatable by 190 degrees,
- ▶ Possibility of checking the content weight while unloading
- ▶ Possibility of using a pneumatic or mechanical loading system
- ► Flexibility in the height of unloading operations,
- ▶ No need of anchoring to the ground, thus more adaptable to "mobile" units
- ► Easy and variable batch of the content
- ► Transportable with no need of special trucks
- ▶ Assembly and disassembly take place in a very short time thanks to 4 swivel feet
- ► Very quick loading/unloading (25mc/h of product)

| Series OR | | | | | | | | | | |
|-----------|-------------------|-------|------|------|------|------|------|------|------|------|
| Code | Capacity | Α | В | С | D | E | F | G | Н | L |
| OR16 | 16 m³ | 4810 | 3000 | 2300 | 4485 | 2271 | 2500 | 2816 | 3250 | 4561 |
| OR26 | 26 m³ | 7506 | 3000 | 2300 | 4485 | 2271 | 2500 | 2816 | 3250 | 4561 |
| OR36 | 36 m³ | 7600 | 3000 | 2492 | 4485 | 2763 | 2992 | 2816 | 3250 | 5053 |
| OR46 | 46 m³ | 9700 | 3000 | 2492 | 4485 | 2763 | 2992 | 2816 | 3250 | 5053 |
| OR56 | 56 m ³ | 11700 | 3000 | 2492 | 4485 | 2763 | 2992 | 2816 | 3250 | 5053 |
| OR66 | 66 m³ | 11950 | 3000 | 2980 | 4485 | 2763 | 2992 | 2816 | 3250 | 5053 |
| OR76 | 76 m³ | 13750 | 3000 | 2980 | 4485 | 2763 | 2992 | 2816 | 3250 | 5053 |













The horizontal silos series "or" can be customized, clients can choose their color and where they can apply their logo and other kinds of customization.

Composition of standard models:

Coated steel body

Support structure with galvanized telescopic legs

219 mm diameter extraction screw with gear motor

219 mm diameter truck loading screw with gear motor

Loading tube

Dust filter

Vibrators or fluidization

Loading cells

Over-vacuum valves

Min /max indicator level


Control panel

E.C. Manual









The horizontal silos series "Flex" can be customized, clients can choose their color and where they can apply their logo and other kinds of customization.


Composition of standard models:

Coated steel body
Loading tube
Venting pipe
Vibrators or fluidization
min / max level indicator
Manual E.C.











| Serie Flex | | | | | | | | |
|------------|------|-------|------|--|--|--|--|--|
| Capacity | А | В | Н | | | | | |
| 40 m³ | 2438 | 12192 | 2591 | | | | | |
| 30 m³ | 2438 | 9125 | 2591 | | | | | |
| 20 m³ | 2438 | 6058 | 2591 | | | | | |







OPTIONALS



Tanke



Loading cells



Fluidization circuit



Blinking light + siren



Electrical panel



Level indicators



Litercounter + pump



Lateral feeding screw holder

ACCESSORIES INCLUDED IN THE SUPPLY



Vibrators



Dust filter



Pressure control valve



Compressor



Emergency button 1



Emergency button 2



Tap off unit